


# ANTI-CONDENSATION HEATERS IP-TMX

## Fan Assisted (Small Footprint) | 150W to 400W

IP Enclosures provide a wide range of heating products for electrical enclosures. Anti-condensation heaters are required to prevent failures or corrosion caused by low temperatures or high humidity inside the enclosure. This occurs when ambient temperature is low and the equipment does not generate enough heat to maintain the minimum internal temperature. IP Enclosures heating products are manufactured to the highest quality in Italy.



| FEATURES                  | UNIT    | IP-TMX150                                                                                  | IP-TMX250 | IP-TMX300 | IP-TMX400 |
|---------------------------|---------|--------------------------------------------------------------------------------------------|-----------|-----------|-----------|
| Heating Capacity          | W       | 150                                                                                        | 250       | 300       | 400       |
| Power Supply              | V/Hz    | 230/50-60                                                                                  | 230/50-60 | 115/50-60 | 115/50-60 |
| Max. current              | A       | -                                                                                          | -         | -         | -         |
| Delayed fuse (advised)    | A       | 6.3                                                                                        | 6.3       | 6.3       | 6.3       |
| Electrical connections    | -       | Spring terminals                                                                           |           |           |           |
| Protection class          | -       | Class II                                                                                   |           |           |           |
| Protection degree EN60529 | -       | IP20                                                                                       |           |           |           |
| Operating temperature     | °C (°F) | -40/+70 (-40/+158)                                                                         |           |           |           |
| Storage temperature       | °C (°F) | -40/+70 (-40/+158)                                                                         |           |           |           |
| Air flow rate             | m³/h    | 30 (free flow)                                                                             |           |           |           |
| Signalling                | -       | -                                                                                          |           |           |           |
| Dimensions HxWxD          | mm      | 88x66x97                                                                                   | 88x66x97  | 88x66x97  | 88x66x97  |
| Weight (with packaging)   | kg      | 0.35                                                                                       | 0.35      | 0.35      | 0.35      |
| Conformity/Certifications | -       | CE-UL  |           |           |           |